



CONSSIN
LIGHTING.CO.LTD

PUBLIC AREA LED STREET LIGHT



DESIGNED FOR USE IN:

- STREET LIGHTS
- CAR PARKS
- TUNNELS
- GENERAL OUTDOOR AREA

MPG1

- INCORPORATED LATEST GENERATION OF 105-115 LM/W CITIZEN CHIP.
- LOW ABSORPTION (LESS THAN 5%) WITH A DIVERGENT-ASYMMETRIC GEOMETRY, GENERATING AN EXTENT AND UNIFORMITY LIGHT BEAM.
- THE NEW LENS IS MADE FROM HIGH PURITY GLASS (96%)
- HIGH UV RESISTANCE AND LOW MAINTENANCE COSTS.
- MADE FROM HIGH QUALITY ALUMINIUM



50000h
Lifetime Range






-40°C ~ +50°C
Working Temperature



100-240AC 24/48DC
Voltage Range



3000K, 4000K, 5000K
Color Temperature



01



MODEL	V	T (kelvin)	LENS	W	LUMEN	MATERIAL	LIGHT Source	Ra	T(H)	Hz	EFFIC	IP	TEMPERATURE (Working)	DIMENSION	WEIGHT
MPG1-025	AC240V	5000K	A D F	25W	2875-3000	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg
MPG1-040	AC240V	5000K		40W	4600-4800	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg
MPG1-060	AC240V	5000K		60W	6900-7200	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg
MPG1-080	AC240V	5000K		80W	8400-9200	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg
MPG1-100	AC240V	5000K		100W	10500-11500	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg
MPG1-120	AC240V	5000K		120W	12600-13800	ALUMINIUM ALLOY	CITIZEN	>70	50000	50/60	92%	IP67	-40°C + 50°C	595mm 273mm 155mm	6.4kg



MORE PRODUCT RANGE ON OUR WEBSITE.